

APPWOOD

PRODUCT PROFILE



ENTRY & EXTERIOR DOORS



From traditional estate style mahogany doors to rustic lake, mountain styles, and industrial or contemporary entry units, AppWood has strived to build on our reputation of producing quality doors and entries designed to complement the character and style of the home.

Our traditionally constructed stile and rail doors start with engineered stiles, known as "Stave Core", built with laminated wood cores, 1/2" thick face skins and solid edges or "staves".

We typically use Select and FAS hardwoods such as Sapele, Spanish Cedar, Alder, Mahogany, White Oak, Poplar, American Black Walnut, Ash,

Pine, Fir, and many more. We work to support responsible forestry by purchasing from FSC Certified dealers. We can also source reclaimed and antique woods for your project.

Your personal designer will also be your Project Manager to manage the important details of your project. Our proven process includes full AutoCAD shop drawings and finish samples for final approvals.

Glass used in our exterior doors are generally 1/2" or 3/4" thick insulated glass units (IG) double glazed with 2 pieces of tempered glass with a bronze spacer. Glass is available in a variety of styles including clear, satin and patterned.

An AppWood exterior door is at least 2 1/4" thick compared to only 1 3/4" in typical factory built doors. Our larger doors can be 3" or more in thickness. Most often we provide our door in a jamb built of matching species, up to 1 5/8" thick, compared to 3/4" on a standard builder grade jamb.



APPWOODDOORS

Handcrafted Doors Since 1998



Additional standard features include:

- Deltana square, 5x5 or 6x6 ball bearing hinges are standard, upgrades at most other door companies.
- 1 ½ x 4 exterior casing finished to match the door with custom casing profiles available.
- Mortise and Tenon joinery
- Hand applied mouldings
- Doors are prepared and provided with entry hardware.
- Solid wood thresholds - 1 ½" thick (for remodels) or 1 ¼" (for new construction) made of Thermal Treated Ash, a sustainable American hardwood treated without chemicals with rot resistance that exceeds that of chemically treated pressure treated woods.
- Premium Silicone rubber weather seals from Resource Conservation Technologies.
- Metal thresholds and brush seals by Pemko, a leader in the industry.
- Our standard exterior finish features 3 coats of Sikkens CETOL® Door & Window satin over wood stain, sealer and glaze. CETOL is a high solids, high performance coating that provides optimum protection and ease of maintenance.



Custom options may include;

- Metal accents in solid colors or patina finishes
- Custom distressing, hand carving
- Specialty finishes
- Decorative and functional Hardware

Visit our website for a gallery of design ideas and inspiration photos
www.AppWoodDoors.com

APPWOOD

Tel. 828-437-4300
info@AppWoodDoors.com
300 Burke Drive
Morganton, NC 28655



APPWOODDOORS

Handcrafted Doors Since 1998

